

POWER THAT LASTS



**CAST-IRON RELIABILITY –
PISTON COMPRESSORS BUILT TO
PERFORM UNDER PRESSURE**

WHY CHOOSE CAST-IRON?

Cast-iron pumps offer unmatched durability and resistance to wear, making them ideal for heavy-duty applications. Their robust construction ensures long service life and reduced maintenance – a smart investment for any industrial setup.

BUILT FOR DEMANDING ENVIRONMENTS

From manufacturing plants, agriculture, pig farming or automotive workshops, these compressors thrive in tough conditions. With thermal stability, low noise and longer duty cycle than aluminum piston compressors, they're ready for your most challenging tasks.



PF5



PF7



PS7

Pump model	Design	Cylinders	Power size		Pressure Bar	Pump RPM	Air displacement l/min	Air delivery Max.
			HP	KW				
SE15V	V-type	2	3	2,2	10	1050	320	210
PF5	V-type	2	4 - 5,5	3 - 4	10	680 - 950	405 - 560	302 - 436
PF7	V-type	2	5,5	4	10	580	500	436
PS7	V-type	3	7,5 - 10	5,5 - 7,5	10	590 - 870	750 - 1100	561 - 814

PERFORMANCE YOU CAN RELY ON

Our piston compressors deliver consistent airflow and pressure, thanks to precision engineering and splash lubrication. Whether in in-line or V-shaped configurations, they're built to perform under pressure – literally.

FLEXIBLE INSTALLATION OPTIONS

Available in floor-mounted versions or on horizontal tanks up to 500 liters, with power ratings up to 10 HP. Choose the setup that fits your space and workflow.

PERFORMANCE DATA

PN	Description	Power Size		Power supply				Tank size	Pump		Pressure	Air displacement	Air delivery
		HP	KW	Voltage	Phase N°	Frequency	DOL/Y-D	Liters	Name	RPM	Bar	l/min	Max.
1839025167	G-MASTER 340-10-90 W	3	2,2	230	1	50	DOL	90	SE15V	1050	10	320	210
1839025168	G-MASTER 400-10-90 D	4	3,0	400	3	50	DOL	90	PF5	680	10	405	302
1839025169	G-MASTER 630-10-90 W	5,5	4,1	400	3	50	DOL	90	PF5	950	10	560	436
1839025170	G-MASTER 620-10-90+90 W	5,5	4,1	400	3	50	DOL	90+90	PF7	580	10	500	436
1839025171	G-MASTER 620-10-270 W	5,5	4,1	400	3	50	DOL	270	PF7	580	10	500	436
1839025173	G-MASTER 760-10-90+90 W	7,5	5,6	400	3	50	DOL	90+90	PS7	590	10	750	561
1839025174	G-Master 760-10-90+90 YD	7,5	5,6	400	3	50	YD	90+90	PS7	590	10	750	561
1839025175	G-MASTER 760-10-270 W	7,5	5,6	400	3	50	DOL	270	PS7	590	10	750	561
1839025176	G-Master 760-10-500 YD	7,5	5,6	400	3	50	YD	500	PS7	590	10	750	561
1839025178	G-Master 1120-10-500 YD	10	7,5	400	3	50	YD	500	PS7	870	10	1100	814

PN	Design			L x H x W	Weight
	Wheels	Handle	Tank Outlet	mm	kg
1839025167	4	HALF	G 1/2	1125 x 890 x 540	85
1839025168	4	HALF	G 1/2	1125 x 940 x 540	120
1839025169	4	HALF	G 1/2	1125 x 940 x 540	120
1839025170	-	-	G 1/2	1030 x 1010 x 750	190
1839025171	-	-	G 1/2	1540 x 1080 x 540	215
1839025173	-	-	G 1/2	1070 x 1030 x 750	235
1839025174	-	-	G 1/2	1070 x 1030 x 750	235
1839025175	-	-	G 1/2	1540 x 1120 x 540	260
1839025176	-	-	G 1/2	1950 x 1250 x 600	300
1839025178	-	-	G 1/2	1950 x 1250 x 600	300



STEP INTO THE FUTURE
OF COMPRESSED AIR

CAST-IRON

www.schneider-airsystems.de

6999230050 © 2026, A.ARIA C. S.r.l. All rights reserved.

A.ARIA C. S.r.l. reserves the right to change or revise specifications and product design in connection with any features of our products. Such changes do not entitle the buyer to corresponding changes, improvements, additions or replacements for equipment previously sold or shipped. Read all safety instructions in the manual before usage.